

center opening (10) jointly receive the log transmitter (12) in a watertight manner; and that the oblong opening (11) and the center opening (10) can be blocked or released by a blocking slide depending on the position of the log transmitter (12), said blocking slide being transversely movable and guided watertight in the head part (9).

22. The device according to claim 21, characterized in that the head part (9) is connected with the sleeve body (4) in a fixed, but detachable manner by means of a threaded ring (9') fixed on the head part.

23. The device according to claim 21, characterized in that in a recess (14) arranged coaxially with the center opening (10), the head part (9) has a sealed sliding ring (15) having axial play against spring force, said sliding ring jointly defining with a plane ring body (17) arranged fixed in the head part (9) and supporting a sealing ring (20) the plane of the blocking slide on the top and bottom sides in a watertight manner.

24. The device according to claim 23, characterized in that the ring body (17) is formed by any desired material and has in an annular groove (19) a sealing ring (20) defining the plane of the blocking slide.

25. The device according to claim 23, characterized in that the sliding ring (15) is supported in a watertight manner, for example on an O-ring made of springy-elastic material, arranged on a sealing ring (16) located in the coaxial recess (14), and displaceable by the sealing ring (16) in the direction of the ring body (17), said O-ring and the ring body (17) jointly keeping the plane of separation closed; and that the sliding ring (15) is movable by a component of the plugging force of the blocking slide (21) acting on the sliding ring (15) transversely to the direction of movement of the blocking slide (21), for releasing the plane of the blocking slide.

B. 26. The device according to claim 23, characterized in that the sliding ring (15) is limited on the underside by an outwardly arched, curved or inclined surface (15') and an inclined inner surface (15'').

27. The device according to claim 25, characterized in that the sealing ring (16) is formed by a springy-elastic plastic, especially foamed plastic.

28. The device according to claim 25, characterized in that a screw spring or similar is tightly supported on the sliding ring (15), and the sliding ring (15) is displaceably in the plane of separation due to the power of the screw spring or similar and is capable of being moved away from the separating plane due to the blocking slide.

29. The device according to claim 21, characterized in that the log transmitter (12) can be sealingly supported by a log transmitter-fast collar (23) in a cover (29) capable of being tightly fastened by a screw winding (29') on the head part (9), and that the log transmitter (12) is fixable by the cover (29) in the longitudinal and middle openings (11, 10) of the sleeve body (4) or head part (9).

30. A device for holding the log transmitter of boat speedometers, comprising a sleeve body arranged in a fixed manner in a perforation in the hull of the boat and having an oblong center opening, in which the log transmitter provided with a fan wheel or the like as the pulse transmitter can be inserted and held in a watertight and detachable manner, characterized in that on the end facing away from the water, the sleeve body (32) supports in a watertight manner a head part (34) having a center opening (31') connected watertight with the oblong opening (39) of the sleeve body (32) and having the same shape and cross sectional size as the latter; that the oblong and the center opening (39; 31') jointly receive the log transmitter in a watertight manner; and that the oblong opening (39) and the center opening (31') can be blocked and released depending on the position of the log transmitter, by means of a blocking element (40) provided with a passage (38) and guided watertight and with swiveling mobility in the head part (34).

31. The device according to claim 29, characterized in that the head part (34) is connected with the sleeve body (32) in a detachable but fixed manner by means of a threaded ring (33) fixed on the head part.

32. The device according to claim 30, characterized in that the head part (34) comprises in a fixed manner a flange (37) extending concentrically in relation to the oblong opening (39) and the center opening (31'), and a blocking element (40) with a passage (38), said blocking element resting watertight on the flange (37) and being capable of swiveling between two end positions, whereby said passage concentrically corresponding in the one end position of the blocking element with the oblong opening (39) and the center opening (31'), and in the other end position being movable into the closing position for closing the oblong opening (39) and the center opening (31').

33. The device according to claim 30, characterized in that on its top side, the flange (37) has a groove (36) for receiving an O-ring (36') serving as the sealing body; and that the blocking member (40) can be placed and guided against the O-ring (36') in a pressure-exerting and sealing manner by means of initial spring tension.

34. The device according to claim 33, characterized in that the initial tension of the spring can be expended by coil springs (41) supported on screw bolts (42, 42') fixed on the head part.

35. The device according to claim 34, characterized in that the blocking element (42) is pivot-mounted on the screw bolt (42) fixed on the head part, and receives and guides in a slide groove the other screw bolt (42') fixed on the head part.

36. The device according to claim 32, characterized in that the blocking element (40) is formed by a plate-shaped, molded component having a sleeve-like attachment (40'') arranged on the side facing away from the sleeve body (32).

B. 37. The device according to claim 32, characterized in that the blocking element (40) is formed from a plastic or from a metallic material.

38. The device according to claim 31, characterized in that the log transmitter is rotatably supportable in, or overlapped by, an apparatus cover which is screwed to the sleeve-like extension (40''), with a collar afixed to the log transmitter.

39. The device according to claim 23, characterized in that the ring body (17) is formed by a suitably plastically deformable material, for example thermoplastic, or by a thermosetting plastic.